

# DACOM

Value-Added Distribution  
for Auto-ID and Mobile Computing

## Thermal DacomPad™

With and Honeywell CN51 mobile terminal and  
Honeywell Thermal RP4 printer

The new innovative solution for the route accounting

All-in-one mobile station including mobile terminal Honeywell  
CN51 and Honeywell RP4 Thermal Printer

Ergonomic  
and easy to  
handle

Rugged and  
resistant

Just 2,6 kg  
weight with  
315 x 305 mm  
dimensions



### CN51 MOBILE TERMINAL HONEYWELL TECHNICAL SPECIFICATIONS

**Processor** Texas Instruments 1.5 GHz  
OMAP 4470 dual core, multi-engine  
processor architecture

**Operating System** Microsoft Windows  
Embedded Handheld v6.5 or Android v4.1\*

**Memory** 1 GB RAM

**Display** 10.16 cm (4.0 in), 480 x 800 pixel  
(WVGA) TFT-LCD display

**Keypad** (27 Key) Numeric or (43 Key) QWERTY  
with backlit keypad

**Environmental:** Rain & Dust Resistance: IP64

**Battery** Smart Battery Pack: 3.7V, 3900 mAh;

**Dimensions** 164 x 74 x 28 mm (base of unit) 32  
mm (top of unit)

**Weight with battery:** 350 g

**Operating Temperature** -10° C to +50° C

**Storage Temperature** -20° C to +70° C

**Decode Capabilities:** All common 1D and 2D  
barcodes; 1D as small as 4 mils; 2D as small  
as 6.6 mils.

**Standard Communications** USB – High Speed  
2.0 Host, USB – High Speed 2.0 Client

#### Integrated Radios

**Wireless WAN Options** UMTS / HSPA

+ (Voice & Data); Flexible Network™  
(Voice & Data); UMTS/HSPA+, CDMA/EV-DO  
Rev A

**Wireless LAN:** Wireless LAN: IEEE®802.11  
a/b/g/n on devices, without Wireless WAN radio;  
IEEE®802.11 b/g/n on cellular devices

**Wireless PAN:** Integrated Bluetooth® Power  
Class 1.5 Version 4 BLE

### THERMAL RP4 PRINT HONEYWELL TECHNICAL SPECIFICATIONS

**Print method** Direct thermal

**Resolution** 203 dpi/8 dots per mm

**Print speed** Max 125 mm per second

**Max print area** 104 mm

**IP54** Certified for resistance to windblown  
water and dust

**Drops** Withstands multiple 2 mt drops to  
concrete

**Communications:** USB 2.0 - Bluetooth  
v.4.0 LE or 802.11 a/b/g/n

**Temperature** Operating—20°C to 50°C

**Power by Battery** 5200 mAh, 7.2V

**Weight** 900 gr.

**Dimensions** 164 mm x 77 mm x 187 mm

**Graphic features** Supports user-defined  
fonts and graphics-including custom logos

## DACOM SpA

Via Pregnana, 32  
20010 Cornaredo (MI)  
Italy  
Ph.+39 (0) 29348151  
Fx.+39 (0) 293481570  
[info@dacomaidc.com](mailto:info@dacomaidc.com)  
[www.dacomaidc.com](http://www.dacomaidc.com)

# Honeywell

THE POWER OF CONNECTED

# Honeywell

THE POWER OF CONNECTED