XT-3815

Specification	XT-3815
Processor	Intel J1900/2GHz up to 2.42GHz/2M Cache (quad core)
System Memory	DDR3L S0-DIMM x 1 max. 8GB,
Storage Device	SATA Storage x 2 (one for HDD/SSD; the other for 1" SSD only) or Optional eMMC module
Power Supply	12V/60W
OS Support	Windows 7/POSReady 7/Windows Embedded 8.1 Industry/DOS/Linux per request/Windows 10 IoT
Connectivity	
LAN Port	10/100/1000Mb x 1
Serial Port	4, 4 on I/O plate (DB9 x 3 + RJ50 x 1)
LIDO D	5V/12V support on all 4 COM ports
UPS Port	Yes
Standard USB Port	7 (1 x USB 3.0 + 6 x USB 2.0)
Audio	Internal 2W speaker x 1
VGA Port	D-SUB, 15 pins, with 12V support for Posiflex monitor
CR Port	1, control 2 CR via optional Y-cable
Parallel Port	1, via optional conversion cable
Diaglas 0 Tayah	
Display & Touch LCD	15" TFT LCD
Resolution	1024 x 768
Touch	True-flat PCAP touch with multi-touch support (IP65 on front panel)
Physical Dimension	
Dimension (W x D x H in mm)	372 x 320 x 252.7
Weight (N.W. in Kg)	5.6
Environment	
Operation Condition	0°C - 40°C, 20%RH - 90%RH (Equipped with HDD); 0°C - 50°C, 20%RH - 90%RH (Equipped with SSD)
Storage Condition	-20°C - 70°C, 10%RH - 90%RH
Options	
SSD	SATA SSD
SA-105	Side Attachment for XT Series with 3 track MSR
SA-205	Side Attachment for XT Series with iButton
SA-305	Side Attachment for XT Series with support for 3 track MSR, RFID and Finger Print Sensor
SA-405	Side Attachment for XT Series with support for 3 track MSR, 3G dongle and Finger Print Sensor
LM-3010	9.7" 1024 x 768 rear-mount 2nd display for XT Series (VGA interface)
LM-3014	14" 1366 x 768 rear-mount wide screen 2nd display for XT Series (VGA interface)
LM-3015	15" 1024 x 768 rear-mount 2nd display for XT Series (VGA interface)
LM-6607	7" 800 x 480 rear-mount 2nd display for XT series (USB interface)
PD-2608UE	2 x 20 VFD, rear-mount, USB with Virtual COM support
PD-350UE	2 x 20 LCD, rear-mount, USB with Virtual COM support
PD-6607	7" color LCD graphical line display, rear-mount (USB interface)
WiFi	Internal mini-PCle WiFi module with PIFA Antenna
	I

^{*}Designed and Manufactured in Taiwan by Posiflex Technology, Inc.



















Fanless POS Terminal





POSIFLEX TECHNOLOGY, INC.

No. 23, Datong St., Tucheng Dist., New Taipei City 23679, Taiwan Tel: +886-2-2268-5577 E-mail: sales@posiflex.com.tw

Fax: +886-2-2268-5388 www.posiflex.com







^{*}The product information and specifications are subject to change without prior notice.
*Please refer to the website for more attachment options.





In today's retail and hospitality market, POS terminal is no longer just a cold and hard business tool. It is a part of the store decoration, a part of the store image. Each curve and detail of the POS terminal should add something to the overall mood of the store, to lift the shopping experience of the customers.

XT-3815 is the new Bay Trail based fanless terminal in the XT family. It is positioned to slot in, performance wise, between XT-3015/3215 running Intel D525 CPU and XT-5315 running Intel Celeron CPU.



Looks

Simmer and sexier than ever, XT Series is a sharp departure from the traditionally more conservative Posiflex terminal design. Every curves and details are carefully thought out to make XT Series one of the most visually desirable terminals in the market.

Flexibility

XT-3815 comes with the selection of two foldable bases, the curvy slim GEN7E Base and the larger but practical GEN8E Base. (U.S Patent 9004436)

The new foldable bases allow XT-3815 to be configured into different configurations. "Flat Folded Mode" to save the shipping package volume. "Low Profile Mode" to allow greater interaction between cashier and the customers; and the traditional "Full Extended Mode" All this can be achieved with a simple pull of the hidden lever. This one terminal/ multi-configurations concept provides unmatched flexibility to store owners and system integrators alike.



Full Extended Mode



Low Profile Mode



Flat Folded Mode

Performance

XT-3815 is equipped with the latest Intel Bay Trail quad core processor that is powerful enough to process anything thrown at it without even breaking a sweat.



Fanless Design

Fanless architecture of XT-3815 allows it to run on harsh environments, such as greasy kitchen, without ever worrying about the fan maintenance. It also allows the machine to run quietly, which is ideally suited for the high-end boutique stores or hospital environment.



GEN8E Base

Optional GEN8E Base that integrates internal power adaptor and PoweredUSB port into the base stand, which allows for clutter free counter.