## XT-4015

Intel Ivy Bridge G1620 CPU, 2.70 GHz, 2M Cache; Intel Ivy Bridge G2120 CPU, 3.10 GHz, 3M Cache; Processor Intel Ivy Bridge Core i3-3220 CPU, 3.30 GHz, 3M Cache; Intel Ivy Bridge Core i5-3550S CPU, up to 3.70 GHz, 6M Cache;
Intel Ivy Bridge Core i7-3770 CPU, up to 3.90 GHz, 8M Cache
System Memory DDR3 SO-DIMM x 2, max. 16GB
Storage Device SATA storage x 2
RAID Function Optional, RAID 1 (Disk Mirroring)
Power Supply 12V/130W
OS Support Win 7/POSReady 7/WE 8.1 Industry/Win 10 loT/Linux per request

#### Display & Touch

LCD	15" TFT LCD
Resolution	1024 x 768
Touch	True-flat PCAP touch with multi-touch support (IP65 on front panel)

#### I/O & Expansion

Serial Port	4, DB9 x 3 + RJ50 x 1, 5V/12V support on all 4 COM ports
Parallel Port	1, via optional conversion cable through service window
Standard USB Port	5, USB 3.0 x 1 + USB 2.0 x 4
PoweredUSB Port	Optional 24V x 1 + 12V x 3 via GEN8E base
LAN Port	10/100/1000 Mb x 2
Display Port	VGA x 1, 12V support for Posiflex monitors
CR Port	1, control 2 CR via optional Y-cable
PS/2 Port	1, via optional conversion cable through service window
UPS Port	Yes
Audio	Internal 2W speaker x 1 + Line-out
Expansion Slot	Mini-PCle slot x 1

## **Physical Dimension**

Dimension (W x D x H in mm)	372 x 320 x 252.7
Weight (N. W. in kg)	6.2

#### Environmental

Operating Condition	0°C - 40°C, 20%RH - 90%RH (Equipped with HDD); 0°C - 50°C, 20%RH - 90%RH (Equipped with SSD)
Storage Condition	-20°C - 70°C, 10%RH - 90%RH

#### **Built-in Options**

-	
WiFi	Mini-PCle WiFi/BT module

#### Attachment Options

POS Monitor	Non-touch TFT LCD: 7" (bezel type)/9.7" (bezel-free/bezel type)/12.1"/14" (bezel-free)/15" (bezel-free/bezel type); PCAP touch TFT LCD: 9.7"/14"/15"; Resistive touch TFT LCD: 15"
Line Display	$2  ext{ x 20 rear-mount VFD/LCD customer line display; 7" color LCD graphical customer line display$
Peripherals	MSR; iButton; Rotatable 2D scanner; RFID; Fingerprint Sensor; Key Keypad

\*Designed and Manufactured in Taiwan by Posiflex Technology, Inc.

\*The product information and specifications are subject to change without prior notice. \*Please refer to the website for more attachment options.

FC

#### Certification

POSIFL

## POSIFLEX TECHNOLOGY, INC.

No. 23, Datong St., Tucheng Dist., New Taipei City 23679, Taiwan Tel : +886-2-2268-5577 E-mail:sales@posiflex.com.tw Fax : +886-2-2268-5388 www.posiflex.com

Flexible! Powerful! Elegant!

# XT-4015

High-End POS Terminal

RoHS

Authorized Distributor / Reseller

Windows\* Embedded







In today's retail and hospitality markets, POS terminal is no longer just a cold and hard business tool. It is a part of the store decoration, a part of the store image. Each curve and detail of the POS terminal should add something to the overall mood of the store, to lift the shopping experience of customers.

The XT-4015 features a 15" true-flat PCAP touch screen, beautifully sculptured slim body, and sexily curved base stand, it looks right at home at any elegantly decorated store. More than just good looks, the XT-4015 can be equipped with the lighting fast Intel Core i7 CPU that provides ample muscle power to handle any task imaginable.

## Sleek Look

The XT-4015 comes from new Posiflex design language. Slimmer than ever, it is a sharp departure from the traditionally conservative Posiflex terminal design. Every curve and detail of the XT-4015 is carefully thought out to make itself one of the most visually desirable terminals in the market.

#### **Powerful Performance**

The XT Series offers a wide range of performances, with the flagship XT-4015 that stands out above everything else. In its heart beats an Intel Core i7 CPU (optional) that is powerful enough to process anything throws at it without even breaking a sweat.

### Multi-Position Folding Base (U.S. Patent 9004436)

The XT-4015 provides the selection of two foldable bases, the curvy slim GEN7E base and the larger but practical GEN8E base. The foldable base can be configured into "Flat Folded Mode" to save the shipping package volume, "Low Profile Mode" to allow greater interaction between the cashier and the customer, and the traditional "Full Extended Mode". All this can be achieved with a simple pull of the hidden lever.



Full Extended Mode

Low Profile Mode



Flat Folded Mode





Power Adaptor

UPS Battery



## Dual LAN



The XT-4015 is equipped with dual LAN ports that allow a dedicated LAN connection for credit card terminal.

## GEN8E Base (U.S. Patent 9004436)

Optional GEN8E base integrates internal power adaptor and PoweredUSB port into the base stand, which keeps counters clutter-free.