



RS35

series

RS35 series



Performance	Operating System	Android 10 (GMS)
	CPU	Octa-core 1.8GHz
	Memory	Default 3GB x 32GB / Optional 4GB x 64GB
	Expansion	Micro SD card slot with SDHC (up to 32GB) and SDXC (up to 2TB) support
	SIM / SAM ¹	2 SIM slots and 1 SAM slot
	Operating Power	Replaceable and rechargeable 3.85V, Li-ion 4000mAh (normal voltage 3.85V / full charge 4.4V / balance mode full charge 4.1V)
	Working Hours ²	minimum 12 hours
	Alert	1 tri-color LED, 1 bi-color LED, vibrator
Wireless Communication	Interface Supported	6-pin I/O & USB 2.0 Type-C with OTG
	WWAN	EDGE/GPRS/GSM: 850/900/1800/1900 UMTS/HSPA+: B1/B2/B4/ B5/B6/B8 FDD LTE: B1/B2/ B3/B4/B5/B7/B8/B12/B13/B17/B19/B20/B25/B26/B28 TDD-LTE: 38/39/40/41 Support VoLTE and Worldwide Band
	WLAN	IEEE 802.11 a/b/g/n/ac/d/h/i
	Additional WLAN Features	802.11r (fast roaming), 802.11 v/k(Voice-Enterprise), CCX (Cisco Compatible Extensions) compatible
	WPAN	Bluetooth® Class I, V4.2 dual mode, V2.1 with Enhanced Data Rate (EDR)
	GPS	GPS/A-GPS/GLONASS/Galileo/Beidou
	Barcode Scanning	2D imager On request: 2D imager tilting angle at 70°
Data Capture	RFID Read / Write	HF RFID 13.56 MHz frequency which supports ISO14443A, ISO14443B, ISO15693, and Felica Support NFC (Peer-to-Peer, Card Reader, Card Emulation)
	Camera	Rear autofocus 13 megapixels with LED flash Front 5 megapixels ³
	Display	5.5" HD+ 720 (W) x 1440 (H), Transmissive IPS LCD, outdoor visibility, optically bonded to Touch Panel
Physical Characteristics	Touch Panel	Corning® Gorilla® Glass, Capacitive touch with stylus or bare or gloved fingertip input, multi-touch CTP water proof support water rejection and wet finger
	Interactive Sensor	Light sensor, Proximity sensor, Motion sensor (Accelerometer, G-sensor), E-compass (Magnetometer), Gyroscope
	Keypad	1 programmable key, volume up and down keys, left and right trigger keys, power key
	Audio	Speaker, microphones with echo and noise cancellation
	Size (LxWxH)	165 x 76.8 x 17.9 mm
	Weight	288 g (with battery)
	Operating Temperature	-20°C to 50°C / -4°F to 122°F
User Environment	Storage Temperature	-30°C to 70°C / -22°F to 158°F (Without battery)
	Humidity (non-condensed)	Operating 10% to 90% / Storage 5% to 95%
	Impact Resistance	IP65 & IP67, 500 tumbles at 0.5 m Standard: 1.5 m (5 ft.) multiple drops onto concrete, 6 drops on each side With rubber boot: 1.8 m (6 ft.) multiple drops onto concrete, 6 drops on each side
	Electrostatic Discharge	± 15 kV air discharge, ± 8 kV contact discharge
	Regularity Compliance	CE, FCC, IC, NCC, TBL, SRRC, CCC, BIS, WPC, WEEE, RoHS, REACH, CA65, BC, nRCAN
Development Support	Android 10.0 SDK, reader API, SAM API, HTML 5 API	
Application Software	ReaderConfig, ButtonAssignment, Mobile Deployment Suite, Software Trigger Key, Xamarin Binding, CipherLab TE, AppLock, HTML5 (Browser and API), SOTI MobiControl, Kalipso, AirWatch, ReMoCloud	
Accessories	Charging and communication cradle, USB snap-on cable, Hand strap, Rubber boot, Pistol grip, 4-slot battery charger, Multi-slot Terminal charging cradle ³ , UHF RFID reader ³ , Vehicle cradle ³	
Warranty	1 year	

1. SAM controller support Mifare SAM security.

2. Minimum 12 hours under WLAN and 2D scanning per 20 seconds, LCD 50% backlight and speaker on (volume is default) at 25°C, RFID off / Bluetooth® off / IEEE 802.11 a/b/g/n/ac on. The test is based on one broadcasting packet per second.

3. Please contact us for availability.

ACCESSORIES



Multi-slot Battery Charger



Single-slot Cradle



Snap-on Cable



Hand Strap



Rubber Boot



Pistol Grip



HEADQUARTERS
CipherLab Co., Ltd.

CipherLab Electronics Trading
(Shanghai) Co., Ltd.

CipherLab USA Inc.

CipherLab Europe

12F, 333 Dunhua S. Rd., Sec.2 Taipei, Taiwan 10669

Tel +886 2 8647 1166 Fax +886 2 8732 3300

JRoom, 4F, No.728 West Yan'an Rd. Changning District, Shanghai China 200050

Tel +86 21 3368 0288 Toll Free +86 400 920 0285 Fax +86 21 3368 0286

2552 Summit Ave. STE 400 Plano, Texas 75074, USA

Tel +1 469 241 9779 Toll Free +1 888 300 9779 Fax +1 469 241 0697

Cahorslaan 24, 5627 BX Eindhoven, The Netherlands

Tel +31 (0) 40 2990202



▲VIDEO



▲WEBSITE